

Qualität Quality Qualité:	PASSION 1001
Konstruktion Construction Description:	1/10“ Getufteter Soft-Frisé 1/10“ Tufted soft frise 1/10“ Frisé soft tufté
Zusatzeignungen/ Additional properties/ Autres propriétés:	
Polnutschicht Pile material Composition de la fibre: Beschichtung Backing Dossier: Grundmaterial Carrier material Composition du support:	100 % PA 6 Ecoback grau/ Ecoback grey/ Ecoback gris 100 % PES
Gesamtgewicht/ Total weight/ Poids total: Poleinsatzgewicht/ Pile weight/ Poids de velours: Polnutschichtgewicht/ Weight of pile material/ Poids du velours utile: Poldicke/ Pile thickness/ Epaisseur du velours : Gesamtdicke/ Total thickness/ Epaisseur totale: Noppenzahl/ Number of tufts/ Nombre de points:	ca. 1950 g/m ² ca. 1170 g/m ² ca. 970 g/m ² ca. 7,5 mm ca. 10,5 mm ca. 1778 dm ²
Trittschallschutz/ Impact noise insulation/ Isolation acoustique Schallabsorptionsgrad/ Sound absorption/ Absorption phonique Wärmedurchlasswiderstand/ Thermal resist./ Résist. Thermique Brandverhalten/ Fire rating/ Comportement au feu Brandklasse/ Fire class/ Classement feu	DIN EN ISO 10140 $\Delta L_w = \geq 25$ dB DIN EN ISO 354 Hz: 125 250 500 1000 2000 4000 α_w : α_s : DIN ISO 8302:1991 $1/\lambda = \leq 0,17$ m ² K/W DIN EN 13501-1 E _{fl}
max. Aufladung/ max. static resistance/ Charge électrique max. Durchgangswiderstand/ Vertical resistance/ Résistance transversale Oberflächenwiderstand/ Surface resistance/ Résistance surfacique Wasserechtheit/ Water fastness/ Comportement à l'eau Farbveränderung/ Colour-changes/ Modification de la couleur Lichtechtheit/ Light fastness/ Comportement à la lumière Reibechtheit/ Rubbing fastness/ Comportement au frottement	DIN EN 1815 Bl.2 $\leq 2,0$ KV DIN ISO/ DIS 10965Bl.1R _{DT} $\leq 10^{10}$ Ω DIN ISO/ DIS 10965Bl.1R _{OT} $\leq 10^{10}$ Ω DIN EN ISO 105-E01 mind. Note/ N./ min.note 4 DIN EN ISO 105-E01 mind. Note/ N./ min.note 4 DIN EN ISO 105-B02 mind. Note/ N./ min.note 5 DIN EN ISO 105-X12 mind. Note/ N./ min.note 4
<div data-bbox="119 1411 399 1792">  <p>18 Vorwerk & Co. Teppichwerke GmbH & Co. KG Kuhlmannstrasse 11 D - 31785 Hameln</p> <p>Tuftingartikel mit Polmaterial PA 6 und Textilrücken</p> <p>EN 1307 DOP: 1062#3/630</p> </div>	